## Foam acoustic absorption member

Patent number:

DE3445656

**Publication date:** 

1986-06-26

Inventor:

**Applicant:** 

IRBIT RESEARCH & CONSULTING AG (CH)

Classification:

- international:

B32B5/18; G10K11/168; B32B5/18; G10K11/00; (IPC1-

7): G10K11/16

- european:

B32B5/18; G10K11/168

Application number: DE19843445656 19841214

Priority number(s): DE19843445656 19841214

Also published as:

EP0185839 (A2) US4715473 (A1)


JP61145598 (A) EP0185839 (A3)

EP0185839 (B1)

Report a data error here

Abstract not available for DE3445656
Abstract of corresponding document: **US4715473** 

A foam acoustic absorption member having a stabilizing layer with perforations and, in order to obtain a simple, stable structural shape of homogeneous resistance to flow, the stabilizing layer (2) is a wide-side wall of a hollow body (K) which wall is pressed, under thermal deformation, against the foam layer (1), the openings in said hollow body consisting of holes (9) punched from the foam side.



Data supplied from the **esp@cenet** database - Worldwide

(5) Int. Cl. 4: G 10 K 11/16



DEUTSCHES PATENTAMT

(2) Aktenzeichen:(2) Anmeldetag:

P 34 45 656.2-53

Offenlegungstag:

14. 12. 84 26. 6. 86

Veröffentlichungstag der Patenterteilung:

28. 1.88

Innerhalb von 3 Monaten nach Veröffentlichung der Erteilung kann Einspruch erhoben werden

- 73 Patentinhaber: Irbit Research + Consulting AG, Freiburg/Fribourg, CH
- (74) Vertreter: Rieder, H., Dr.rer.nat., Pat.-Anw., 5600 Wuppertal
- (7) Erfinder:
  Antrag auf Nichtnennung
- Für die Beurteilung der Patentfähigkeit in Betracht gezogene Druckschriften:

DE 33 36 850 A1 DE 33 01 682 A1 DE 32 15 244 A1

Schaumstoff-Schallabsorptionskörper

**JE 3445656 C 2** 

BUNDESDRUCKEREI 12, 87 708 164/322



Foam acoustic absorption member						
Veröffentlichungsnr. (Sek.)	□ <u>US4715473</u>					
Veröffentlichungsdatum :	1987-12-29					
Erfinder:	TSCHUDIN-MAHRER ROLF [CH]					
Anmelder :	IRBIT RESEARCH & CONSULTING AG [CH]					
Veröffentlichungsnummer :	DE3445656					
Aktenzeichen: (EPIDOS-INPADOC-normiert)	US19850807614 19851211					
Prioritätsaktenzeichen: (EPIDOS-INPADOC-normiert)	DE19843445656 19841214					
Klassifikationssymbol (IPC):	E04B1/82					
Klassifikationssymbol (EC):	B32B5/18, G10K11/168					
Korrespondierende Patentschriften EP0185839, A3, B1, D JP61145598						
Bibliographische Daten						
A foam acoustic absorption member having a stabilizing layer with perforations and, in order to obtain a simple, stable structural shape of homogeneous resistance to flow, the stabilizing layer (2) is a wide-side wall of a hollow body (K) which wall is pressed, under thermal deformation, against the foam layer (1), the openings in said hollow body consisting of holes (9) punched from the foam side.						
Daten aus der esp@cenet Datenbank I2						

## United States Patent [19]

## Tschudin-Mahrer

[11] Patent Number:

4,715,473

[45] Date of Patent:

Dec. 29, 1987

		<del> </del>			<del></del>	
[54]	FOAM AC	OUSTIC ABSORPTION MEMBER	4,253,543		Johansson .	
[75]	Inventor:	Rolf Tschudin-Mahrer, Lausen, Switzerland	4,584,232 4/1986 Frank et al 181/288 FOREIGN PATENT DOCUMENTS			
[73]	Assignee:	Irbit Research & Consulting AG, Fribourg, Switzerland	W08402998 1154923 2735153	9/1963	European Pat. Off Ped. Rep. of Germany . Fed. Rep. of Germany 181/288	
[21]	Appl. No.:	807,614	2937389	4/1981	Fed. Rep. of Germany .	
[22]	Filed:	Dec. 11, 1985	1510712	5/1978	United Kingdom .	
[30]	Foreig	n Application Priority Data	Primary Examiner—Bernard Nozick Attorney, Agent, or Firm—Martin A. Farber			
Dec. 14, 1984 [DE] Fed. Rep. of Germany 3445656			[57] ABSTRACT			
[51]	Int, Cl.4	•				
[52]	U.S. Cl	A foam acoustic absorption member having a stabilizing layer with perforations and, in order to obtain a simple,				
[58]	428/137, 138; 181/286, 288, 291, 292, 293; flow, the stabilizing layer (2) is a wide-side wall of 264/515, 516 hollow body (K) which wall is pressed, under therm					
[56]	References Cited U.S. PATENT DOCUMENTS		deformation, against the foam layer (1), the openings in said hollow body consisting of holes (9) punched from the foam side.			

1 Claim, 4 Drawing Figures

